

FENIX

CCTV SECURITY SYSTEMS

High Definition Transport Video Interface



New Generation of
High Definition Technology
Over Coaxial Cable



FX-6316LT

- 3 Megapixel high-performance CMOS
- Analog HD output, up to 3MP resolution
- True Day/Night
- OSD menu, DNR, Smart IR
- EXIR technology, up to 20/40/80m IR distance
- IP66 weatherproof
- Up the Coax(HIKVISION-C)



FX-6316ST

- 3 Megapixel high-performance CMOS
- Analog HD output, up to 3MP resolution
- True Day/Night
- OSD menu, DNR, Smart IR
- EXIR technology, up to 20m IR distance
- IP66 weatherproof
- Up the Coax(HIKVISION-C)



FX-6315ST

- 3 Megapixel high-performance CMOS
- Analog HD output, up to 3MP resolution
- True Day/Night
- OSD menu, DNR, Smart IR
- EXIR technology, up to 20m IR distance
- IP66 weatherproof
- Up the Coax(HIKVISION-C)



FX-6226LT

- 2 Megapixel high-performance CMOS
- Analog FULL HD output, up to 1080P resolution
- 2.8 – 12mm vari-focal lens
- True Day/Night, Smart IR
- Up to 40m IR distance
- OSD Menu, Control by DVR
- 3D-DNR, BLC, EIS, OSD, IP-66 weatherproof
- Up the Coax



FX-6216LT

- 2 Megapixel high-performance CMOS
- Analog FULL HD output, up to 1080P resolution
- Lens : 3.6mm (2.8mm optional)
- True Day/Night, Smart IR
- EXIR Technology, up to 20m IR distance
- OSD Menu, Control by DVR
- 3D-DNR, BLC, EIS, OSD, IP-66 weatherproof
- Up the Coax



FX-6216ST

- 2 Megapixel high-performance CMOS
- FULL HD output, up to 1080P resolution
- Lens : 3.6mm (2.8mm optional)
- True Day/Night, Smart IR
- Up to 20m IR distance
- OSD Menu, Control by DVR
- 3D-DNR, BLC, EIS, OSD, IP-66 weatherproof
- Up the Coax



FX-6225LT

- 2 Megapixel high-performance CMOS
- Analog FULL HD output, up to 1080P resolution
- 2.8 – 12mm vari-focal lens
- True Day/Night, Smart IR
- Up to 40m IR distance
- OSD Menu, Control by DVR
- 3D-DNR, BLC, EIS, OSD, IP-66 weatherproof
- Up the Coax



FX-6215LT

- 2 Megapixel high-performance CMOS
- Analog FULL HD output, up to 1080P resolution
- Lens : 3.6mm (2.8mm optional)
- True Day/Night, Smart IR
- EXIR Technology, up to 20m IR distance
- OSD Menu, Control by DVR
- 3D-DNR, BLC, EIS, OSD, IP-66 weatherproof
- Up the Coax



FX-6215ST

- 2 Megapixel high-performance CMOS
- Analog FULL HD output, up to 1080P resolution
- Lens : 3.6mm (2.8mm optional)
- True Day/Night, Smart IR
- Up to 20m IR distance
- OSD Menu, Control by DVR
- 3D-DNR, BLC, EIS, OSD, IP-66 weatherproof
- Up the Coax



FX-6237SP

- HD1080p, 1/3" CMOS, TVI & CVBS dual output
- 3D DNR, ICR,
- Color: 0.05lux/F1.4, B/W:0.005lux/F1.4,
- Optical Zoom:23x, Focus:4.0-92mm,
- Digital Zoom:16X, Pan range:360° endless, Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -120°/s
- Up the Coax
- 150m IR





FX-426SF

- 2.4MP AHD, 1/2.7" Sony CMOS Sensor
- IR Cut,DWDR,3DDNR, OSD , AWB, AGC, BLC
- V/F Lens 2/8~12mm 3MP
- IR range:45M
- IP66, outdoor installation



FX-416SP

- 2.1MP AHD, 1/2.7" Sony CMOS Sensor
- IR Cut,DWDR,3DDNR, OSD , AWB, AGC, BLC
- Fixed Lens Lens 3.6mm 3MP
- IR range:35M
- IP66, outdoor installation



FX-416SD

- 2.1MP AHD, 1/2.7" Sony CMOS Sensor
- IR Cut,DWDR,3DDNR, OSD , AWB, AGC, BLC
- Fixed Lens Lens 3.6mm 3MP
- IR range:20M
- IP66, outdoor installation



FX-425SF

- 2.4MP AHD, 1/2.7" Sony CMOS Sensor
- IR Cut,DWDR,3DDNR, OSD , AWB, AGC, BLC
- V/F Lens 2/8~12mm 3MP
- IR range:45M
- IP66, outdoor installation



FX-415SP

- 2.1MP AHD, 1/2.7" Sony CMOS Sensor
- IR Cut,DWDR,3DDNR, OSD , AWB, AGC, BLC
- Fixed Lens Lens 3.6mm 3MP
- IR range:30
- IP66, outdoor installation



FX-415SD

- 2.1MP AHD, 1/2.7" Sony CMOS Sensor
- IR Cut,DWDR,3DDNR, OSD , AWB, AGC, BLC
- Fixed Lens Lens 3.6mm 3MP
- With SMD IR
- IP66, outdoor installation

DVR

HD - TVI

5 in 1



FX-7104EH

- 4CH TVI/CVI/AHD/Analog & IP Cameras
- H.264+ / H.264 Video compression
- Support 3MP Real Time/PLAY & RECORD 720P , 1080P LITE REAL TIME AND 1080P 12.5 FPS
- HDMI and VGA output at up to 1920 x 1080
- Long Transmission distance over coax cable



FX-7108EH

- 8CH TVI/CVI/AHD/Analog & IP Cameras
- H.264+ / H.264 Video compression
- Support 3MP Real Time/PLAY & RECORD 720P , 1080P LITE REAL TIME AND 1080P 12.5 FPS
- HDMI and VGA output at up to 1920 x 1080
- Long Transmission distance over coax cable



FX-7216EH

- 16CH TVI/CVI/AHD/Analog & IP Cameras
- H.264+ / H.264 Video compression
- Support 3MP Real Time/PLAY & RECORD 720P , 1080P LITE REAL TIME AND 1080P 12.5 FPS
- HDMI and VGA output at up to 4K 3840 x 2160P
- Long Transmission distance over coax cable

DVR


XVR

5 in 1



FX-XVR5104

- 4ch 1080N@25fps Recording
- Support AHD/TVI/CVI/CVBS/IP
- Support: 1 x HDD up to 6TB
- 4-CH Audio IN
- HDMI , VGA , LAN , Audio Output
- CMS , Web View and MobileView



FX-XVR5108

- 8ch 1080N@25fps Recording
- Support AHD/TVI/CVI/CVBS/IP
- Support: 1 x HDD up to 6TB
- 4-CH Audio IN
- HDMI , VGA , LAN , Audio Output
- CMS , Web View and MobileView



FX-XVR5216

- 16ch 1080N@25fps Recording
- Support AHD/TVI/CVI/CVBS/IP
- Support: 1 x HDD up to 6TB
- 8-CH Audio IN
- HDMI , VGA , LAN , Audio Output
- CMS , Web View and MobileView



FX-XVR5416

- 16ch 1080N@25fps Recording
- Support AHD/TVI/CVI/CVBS/IP
- Support: 4 x HDD up to 6TB
- 16-CH Audio IN
- HDMI , VGA , LAN , Audio Output
- CMS , Web View and MobileView



FX-XVR5432

- 32ch 1080N@25fps Recording
- Support AHD/TVI/CVI/CVBS/IP
- Support: 4 x HDD up to 6TB
- 16-CH Audio IN
- HDMI , VGA , LAN , Audio Output
- CMS , Web View and MobileView





High Definition Transport Video Interface



FENIX
CCTV SECURITY SYSTEMS